



DECLARACIÓN DE PRESTACIONES
No.NGR-T1

1. Código de identificación única del producto tipo
Tipo, lote o número de serie o de cualquier otro elemento que permita la identificación del producto
Baldosas cerámicas prensadas en seco, con absorción de agua $E_b \leq 0,5\%$
2. Uso o usos previstos
Para suelos y paredes interiores y exteriores
3. Nombre o marca registrada de fabricante y dirección del fabricante
NAVARTI CERAMICA, S.L.U.
Ctra. Onda-Villarreal, Km 3,5
12200 Onda (Castellón) ESPAÑA
4. Sistema o sistemas de evaluación y verificación de la constancia de prestaciones
Sistema 4
5. Nombre y número de laboratorio notificado, si procede – **no procede**
Tarea realizada
Sistema de evaluación
Documento emitido y fecha de emisión
6. Prestaciones declaradas

Características esenciales	Prestaciones	Especificación técnica armonizada
Reacción al fuego	A1 _{FL} /A1	EN 14411:2012
Emisión de sustancias peligrosas:		
- Cadmio	PND	
- Plomo	PND	
Fuerza de rotura	> 1 300 N	
Deslizamiento:	PND	
Propiedades táctiles	PND	
Adhesión:		
Adhesivo cementoso tipo C2	> 1 N/mm ²	
Resistencia al choque térmico	Cumple	
Durabilidad para:		
- usos interiores:	Cumple	
- usos exteriores: resistencia a la helada	Cumple	

Las prestaciones del producto identificado en el punto 1 son conformes con las prestaciones declaradas en el punto 6.

La presente declaración de prestaciones se emite bajo la única responsabilidad del fabricante indicado en el punto 3.

Firmado por y en nombre del fabricante por:

Jaime Bausá (Gerente)
Nombre y cargo

Onda, 01-03-2014
Lugar y fecha de emisión

Firma



DECLARATION OF PERFORMANCE
No. NGR-T1

1. Unique identification code of the product type
Type, batch or serial number or any other element allowing identification of the product
Dry-pressed ceramic tiles, with low water absorption $E_b \leq 0,5 \%$
2. Intended use(s)
For internal and external, floorings and wall finishes
3. Name or registered trade mark, and contact address of the manufacturer
NAVARTI CERAMICA, S.L.U.
Ctra. Onda-Villarreal, Km 3,5
12200 Onda (Castellón) SPAIN
4. System(s) of assessment and verification of constancy of performance (AVCP)
Systems 4
5. Name and identification number of notified laboratory, if relevant – **not applicable**
Task(s) carried out
AVCP system
Document issued and date of issue
6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL} /A1	EN 14411:2012
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 1 300 N	
Slipperiness	NPD	
Tactility	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C2	> 1 N/mm ²	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.
Signed for and on behalf of the manufacturer by:

Jaime Bausá (Manager)
Name and function